

Description

Fastener Length: 1-9/16", Thread: 3/8-24, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN176C14
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-609-5982
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN176C14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.640 Inches Nominal
Fastener Length:	1.578 Inches Nominal
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Grip Diameter:	0.3737 Inches Minimum And 0.3742 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum And 0.116 Inches Maximum First Hole
End Item Identification:	Aircraft,air Force
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.938 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Yield Strength:	7740 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.376 Inches Nominal First Hole
Surface Finish:	63.0 Microinches Fastener
Part Name Assigned By Controlling Agency:	Bolt,machine,close Tolerance,aircraft
Material:	Steel Corrosion Resisting Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/AN176C14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.