

Description

Fastener Length: 2-31/64", Thread: 3/8-24, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN176C23A |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-107-7238 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN176C23A Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.611 Inches Minimum And 0.687 Inches Maximum |
| Fastener Length: | 2.438 Inches Minimum And 2.484 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.203 Inches Minimum And 0.235 Inches Maximum |
| Width Between Flats: | 0.553 Inches Minimum And 0.565 Inches Maximum |
| Grip Diameter: | 0.3737 Inches Minimum And 0.3742 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 1.797 Inches Minimum And 1.827 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Surface Finish: | 63.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 63.0 Microinches Grip |
| Material: | Steel Comp 431 Overall |
| Material Document And Classification: | Mil-s-18732 Mil Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/AN176C23A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.