

P/N AN176H11A

Description

Fastener Length: 1-15/64", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: AN176H11A

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-639-2379

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN176H11A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.609 Inches Minimum And 0.688 Inches Maximum
Fastener Length:	1.187 Inches Minimum And 1.234 Inches Maximum
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.565 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Grip Diameter:	0.3737 Inches Minimum And 0.3742 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.546 Inches Minimum And 0.578 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

How to Order

