

Description

length: 61/64", grip: 5/16", thread: 3/8-24, cadmium plated steel undrilled shank - drilled head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN176H7A
Minimum Qty (MOQ):	1
NSN:	5306-00-928-2360
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN176H7A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.609 Inches Minimum And 0.688 Inches Maximum
Fastener Length:	0.937 Inches Minimum And 0.984 Inches Maximum
Head Style:	Hexagon
Head Height:	0.203 Inches Minimum And 0.235 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.556 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Grip Diameter:	0.3737 Inches Minimum And 0.3742 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.296 Inches Minimum And 0.328 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/AN176H7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.