

**Description**

Fastener Length: 3-23/64", Thread: 7/16-20, Thread Length: 17/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN177C32
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-301-3756
Schedule B:	7318.15.8085
ECCN:	9A991



\* See page 2 for technical characteristics

## P/N AN177C32 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.535 Inches Nominal
<b>Fastener Length:</b>	3.310 Inches Minimum And 3.372 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.234 Inches Minimum And 0.266 Inches Maximum
<b>Width Between Flats:</b>	0.720 Inches Nominal
<b>Grip Diameter:</b>	0.4362 Inches Minimum And 0.4367 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.438 Inches
<b>Grip Length:</b>	2.667 Inches Minimum And 2.697 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	88044-an177 Government Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/AN177C32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.