

Description

Fastener Length: 1-3/4", Hole Diameter: 1/16", Thread: 3/8-20, Thread Length: 45/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN177H15 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-639-2349 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN177H15 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.625 Inches Minimum And 0.704 Inches Maximum |
| Fastener Length: | 1.703 Inches Minimum And 1.750 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.234 Inches Minimum And 0.266 Inches Maximum |
| Width Between Flats: | 0.615 Inches Minimum And 0.627 Inches Maximum |
| Hole Diameter: | 0.070 Inches Nominal |
| Grip Diameter: | 0.4362 Inches Minimum And 0.4367 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.106 Inches Nominal First Hole |
| Nominal Thread Diameter: | 0.437 Inches |
| Grip Length: | 1.046 Inches Minimum And 1.078 Inches Maximum |
| Hole Quantity: | 1 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Hexagon Flats |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.546 Inches Nominal First Hole |
| Surface Finish: | 63.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 63.0 Microinches Grip |
| Material: | Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/AN177H15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.