

Description

Fastener Length: 3-5/16", Thread: 3/4-16, Thread Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN182C31
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-936-2996
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN182C31 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.062 Inches Minimum And 1.140 Inches Maximum
Fastener Length:	3.265 Inches Minimum And 3.312 Inches Maximum
Head Style:	Hexagon
Head Height:	0.390 Inches Minimum And 0.422 Inches Maximum
Width Between Flats:	1.053 Inches Minimum And 1.066 Inches Maximum
Grip Diameter:	0.7481 Inches Minimum And 0.7488 Inches Maximum
Shank Unthreaded Hole Diameter:	0.141 Inches Minimum First Hole And 0.151 Inches Maximum First Hole
Nominal Thread Diameter:	0.750 Inches
Grip Length:	2.172 Inches Minimum And 2.203 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.052 Inches Minimum First Hole And 2.072 Inches Maximum First Hole
Material:	Steel Comp 431 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN182C31> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.