

**Description**

Fastener Length: 3-13/32", Thread: 3/4-16, Thread Length: 1-3/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN182C32                                  |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-00-957-2294                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N AN182C32 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 1.094 Inches Minimum  |
| <b>Fastener Length:</b>   | 3.406 Inches Nominal  |
| <b>Head Style:</b>  | Hexagon   |
| <b>Head Height:</b>   | 0.390 Inches Minimum And 0.422 Inches Maximum                       |
| <b>Width Between Flats:</b>   | 1.053 Inches Minimum And 1.066 Inches Maximum                       |
| <b>Grip Diameter:</b>   | 0.7481 Inches Minimum And 0.7488 Inches Maximum                     |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.141 Inches Nominal First Hole                                     |
| <b>Nominal Thread Diameter:</b>   | 0.750 Inches  |
| <b>Grip Length:</b>   | 2.312 Inches Nominal  |
| <b>Thread Quantity Per Inch:</b>  | 16  |
| <b>Minimum Tensile Strength:</b>  | 125000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>   | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 3.187 Inches Nominal First Hole                                     |
| <b>Surface Finish:</b>  | 63.0 Microinches Bearing Surface Of Head                            |
| <b>Surface Finish:</b>  | 63.0 Microinches Grip   |
| <b>Material:</b>  | Steel Comp 431 Overall  |
| <b>Material Document And Classification:</b>                            | Mil-s-18732 Mil Spec Single Material Response Overall               |
| <b>Surface Treatment:</b>   | Passivate Overall   |
| <b>Surface Treatment Document And Classification:</b>                   | Mil-b-6812 Mil Spec Single Treatment Response Overall               |
| <b>Thread Series Designator:</b>  | Unf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN182C32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.