

P/N AN23-13

Military-Fasteners.com

#### Description

length: 27/32", grip: 1/2", thread: 10-32, cadmium plated steel, drilled shank

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

### **Additional Information**

SKU / Model:	AN2313
Minimum Qty (MOQ):	20
NSN:	5306-00-151-1965
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N AN23-13 Specifications

Thread Direction:Right-handThread Length:0.297 Inches MinimumFasteer Length:0.297 Inches MinimumFasteer Length:0.844 Inches NominalHead Style:ButtonaHead Diameter:0.359 Inches Minimum And 0.391 Inches MaximumHead Height:0.078 Inches Minimum And 0.110 Inches MaximumGroove Diameter:0.141 Inches NominalShak Unthreaded Hole Diameter:0.707 Inches Minimum First Hole And 0.080 Inches Miximum First HoleSingle Shear Strength:1215 Pounds Per Square InchInternal Drive Style:SlotNominal Thread Diameter:0.190 Inches0.190 Inches1.90 InchesNeminal Strateger To Shank Hole0.688 Inches Nominal First HoleDistance From Head Largest0.688 Inches Nominal First HoleBaering Surface To Shank Hole0.688 Inches Nominal First HoleCenter:0.688 Inches Nominal First HoleCharterial Document And Classification:Mil-s-6049 Mil Spec 13t Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6059 Mil Spec 3nd Mater		
Thread Length:2.97 Inches MinimumFastener Length:0.844 Inches NominalHead Style:ButtonHead Diameter:0.359 Inches Minimum And 0.391 Inches MaximumHead Height:0.378 Inches Minimum And 0.110 Inches MaximumGrove Diameter:0.141 Inches NominalShank Unthreaded Hole Diameter:0.070 Inches Minimum First Hole And 0.080 Inches Maximum First HoleSingle Shear Strength:125 Pounds Per Square InchInternal Drive Style:SotNominal Thread Diameter:1.900 InchesJob Inches1.900 InchesThread Quartity Per Inch:3Saterial Surface To Shank HoleSteel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mili-s-6049 Mili Spec 1st Material Response Overall Or Mili-s-6050 Mili Spec 2nd Material Response Overall Or Mili-s-6058 Mili Spec 3th Material Response Overall Or Mili-s-6058 Mi	Thread Class:	За
Fastener Length:0.844 Inches NominalHead Style:ButtonHead Diameter:0.359 Inches Minimum And 0.391 Inches MaximumHead Diameter:0.078 Inches Minimum And 0.101 Inches MaximumGroove Diameter:0.141 Inches NominalGroove Diameter:0.141 Inches NominalShank Unthreaded Hole Diameter:0.100 Inches Minimum First Hole And 0.080 Inches Maximum First HoleSingle Shear Strength:0.125 Pounds Per Square InchInternal Drive Style:SlotNominal Thread Diameter:0.190 Inches0.190 Inches32Distance From Head Largest Bearing Surface To Shank HoleSell Inches Nominal First HoleNaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 OverallMaterial:Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Mil-s-6058 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6058 Mil Spec 3rd Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6558 Mil Spec 5th Material Response Overall Or Mil-s-6558 Mil Spec 5th Material Response Overall Mil-s-6659 Mil Spec 6th Material Response Overall Or Mil-s-6558 Mil Spec 5th Material Response Overall Mil-s-6659 Mil Spec 6th Material Response OverallSurface Treatment toCadmiun Overall And Chromate OverallSurface Treatment toCadmiun Overall And Chromate OverallSurface Treatment toCadmiun Overall And Chro	Thread Direction:	Right-hand
Head Style:ButtonHead Diameter:0.359 Inches Minimum And 0.391 Inches MaximumHead Height:0.778 Inches Minimum And 0.110 Inches MaximumGroove Diameter:0.141 Inches NominalShank Unthreaded Hole Diameter0.070 Inches Minimum First Hole And 0.080 Inches Maximum First HoleSingle Shear Strength:2125 Pounds Per Square InchInternal Drive Style:SlotNominal Thread Diameter:0.190 Inches0.190 Inches32Postance From Head Largest Bearing Surface To Shank HoleSele Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mili-s-6049 Mil Spec 1 st Material Response Overall Or Mil-s-6050 Mil Spec 2 nd Material Response Overall Or Mil-s-6050 Mil Spec 2 nd Material Response Overall Or Mil-s-6050 Mil Spec 2 nd Material Response Overall Or Mil-s-6050 Mil Spec 2 nd Material Response Overall Or Mil-s-6050 Mil Spec 2 nd Material Response Overall Or Mil-s-6050 Mil Spec 2 nd Material Response Overall Or Mil-s-6050 Mil Spec 2 nd Material Response Overall Or Mil-s-6050 Mil Spec 2 nd Material Response Overall Or Mil-s-6050 Mil Spec 5 Mil Spec 5 Mil Material Response Overall Or Mil-s-6050 Mil Spec 5 Mil Spec 5 Mil Material Response Overall Or Mil-s-6050 Mil Spec 5 Mil S	Thread Length:	0.297 Inches Minimum
Head Dameter:0.359 Inches Minimum And 0.391 Inches MaximumHead Height:0.078 Inches Minimum And 0.110 Inches MaximumGroove Diameter:0.141 Inches NominalShank Unthreaded Hole Diameter:0.070 Inches Minimum First Hole And 0.080 Inches Maximum First HoleSingle Shear Strength:212 Pounds Per Square InchInternal Drive Style:StoNominal Thread Quantity Per Inch:32JStance From Head Largest Bearing Surface To Shank Hole Center:Stel Comp 8740 Overall Or Stel Comp 8630 Overall Or Stel Comp 8735 Overall Or Stel Comp 4037 OverallMaterial Encoment And Classification:Mile-Soday Mil Spec 1st Material Response Overall Or Mile-Sofos Mil Spec 2nd Material Response Overall Or Mile-Sofos Mil Spec 5th Material Response OverallSurface Treatment Socument And Cassification:Galum Overall And Chromate OverallSurface Treatment Socument Material Response Overall Or Mile-Sofos Mil Spec 2nd Material Response Overall Or Mile-Sofos Mile Spec 5th Material R	Fastener Length:	0.844 Inches Nominal
Head Height:0.78 Inches Minimum And 0.110 Inches MaximumGroove Diameter:0.141 Inches NominalShank Unthreaded Hole Diameter:0.70 Inches Minimum First Hole And 0.080 Inches Maximum First HoleSingle Shear Strength:125 Pounds Per Square InchInternal Drive Style:SotNominal Thread Diameter:190 InchesJistance From Head Largest Bearing Surface To Shank Hole32Naterial:0.688 Inches Nominal First HoleMaterial:0.688 Inches Nominal First HoleMaterial:0.688 Inches Nominal First HoleSteel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8630 Overall Or Steel Comp 8630 Overall Or Miles-6050 Mil Spec 2nd Material Response Overall Or Miles-6050 Mil Spec 3th Material Response Overall Or Miles-6050 Mil Spec 2nd Material Response Overall Or Miles-6050 Miles Spec 3th Material Respons	Head Style:	Button
Groove Diameter:0.141 Inches NominalShank Unthreaded Hole Diameter:0.070 Inches Minimum First Hole And 0.080 Inches Maximum First HoleSingle Shear Strength:2125 Pounds Per Square InchInternal Drive Style:SlotNominal Thread Diameter:0.190 Inches0.190 Inches32Distance From Head Largest Bearing Surface To Shank Hole0.688 Inches Nominal First HoleMaterial Document And Classification:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4037 OverallSurface Treatment Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil	Head Diameter:	0.359 Inches Minimum And 0.391 Inches Maximum
Shank Unthreaded Hole Diameter0.070 Inches Minimum First Hole And 0.080 Inches Maximum First HoleSingle Shear Strength:125 Pounds Per Square InchInternal Drive Style:StoNominal Thread Diameter:0.190 InchesJob Inches3Distance From Head Largest Bearing Surface To Shank Hole Center:0.688 Inches Nominal First HoleMaterial:Stel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallMaterial:Stel Comp 8740 Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6698 Mil Spec 3th Material Response OverallSurface Treatment:Camium Overall And Chromate OverallSurface Treatment Document And Classification:Orp-9416 Ty 2 Cl 3 Fed Spec Single Treatment Response OverallMarea Streate Document And Classification:Orp-9416 Ty 2 Cl 3 Fed Spec Single Treatment Response OverallMarea Treatment Document And Classification:Orp-9416 Ty 2 Cl 3 Fed Spec Single Treatment Response OverallMarea Streate Treatment:Unf	Head Height:	0.078 Inches Minimum And 0.110 Inches Maximum
Single Shear Strength:2125 Pounds Per Square InchInternal Drive Style:SlotNominal Thread Diameter:.190 InchesThread Quantity Per Inch:32Distance From Head Largest Bearing Surface To Shank Hole Center:.688 Inches Nominal First HoleMaterial:.688 Inches Nominal First HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 OverallMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 OverallMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 OverallMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 OverallMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec 4th Material Response Overall Or Mil-s-6059 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:q-p416 Ty 2 Cl 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf	Groove Diameter:	0.141 Inches Nominal
Internal Drive Style:SlotNominal Thread Diameter:0.190 InchesThread Quantity Per Inch:32Distance From Head Largest Bearing Surface To Shank Hole0.688 Inches Nominal First HoleCenter:0.688 Inches Nominal First HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf	Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Nominal Thread Diameter:0.190 InchesThread Quantity Per Inch:32Distance From Head Largest Bearing Surface To Shank Hole0.688 Inches Nominal First HoleMaterial:0.688 Inches Nominal First HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf	Single Shear Strength:	2125 Pounds Per Square Inch
Thread Quantity Per Inch:32Distance From Head Largest Bearing Surface To Shank Hole center:0.688 Inches Nominal First HoleMaterial:0.seel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4037 OverallMaterial Document And classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6058 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And classification:Q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response OverallMaterial Series Designator:Unf	Internal Drive Style:	Slot
Distance From Head Largest Bearing Surface To Shank Hole0.688 Inches Nominal First HoleMaterial:0.688 Inches Nominal First HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallQu-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response OverallOurThread Series Designator:Unf	Nominal Thread Diameter:	0.190 Inches
Bearing Surface To Shank Hole0.688 Inches Nominal First HoleMaterial:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallQuep-416 Ty 2 Cl 3 Fed Spec Single Treatment Response OverallOrerall Classification:Thread Series Designator:Unf	Thread Quantity Per Inch:	32
Center:Image: Center:Material:Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6058 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response OverallMineral Response OverallMil-sed Spec Single Treatment Response Overall	Distance From Head Largest Bearing Surface To Shank Hole	0.688 Inches Nominal First Hole
Material:Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response OverallSurface Treatment Document And 		
Material Document And Classification:Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf	Material:	
Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall   Thread Series Designator: Unf	Material Document And Classification:	Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or
Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall   Thread Series Designator: Unf	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Departure From Cited Document: Thread T Per M1I-s-7742 Except Major D1a Is Not To Exceed Max Allow Bolt Shank D1a	Thread Series Designator:	Unf
	Departure From Cited Document:	Thread T Per M1I-s-7742 Except Major D1a Is Not To Exceed Max Allow Bolt Shank D1a

# How to Order

Order this clevis bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/clevis+bolts/AN23-13</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.