

P/N AN23-13

Description

length: 27/32", grip: 1/2", thread: 10-32, cadmium plated steel, drilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN2313

Minimum Qty (MOQ): 20

NSN: 5306-00-151-1965

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN23-13 Specifications

3a
Right-hand
0.297 Inches Minimum
0.844 Inches Nominal
Button
0.359 Inches Minimum And 0.391 Inches Maximum
0.078 Inches Minimum And 0.110 Inches Maximum
0.141 Inches Nominal
0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
2125 Pounds Per Square Inch
Slot
0.190 Inches
32
0.688 Inches Nominal First Hole
Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Unf
Thread T Per M1I-s-7742 Except Major D1a Is Not To Exceed Max Allow Bolt Shank D1a

How to Order

Order this clevis bolt from our inventory online by visiting https://military-fasteners.com/bolts/clevis+bolts/AN23-13 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/clevis+bolts/AN23-13 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/clevis+bolts/AN23-13 and selecting the quantity you want then click "add to cart".