

**Description**

length: 1-19/32", grip: 1-1/4", thread: 10-32, cadmium plated steel undrilled shank

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN2325A                                   |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5306-00-156-2527                          |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N AN23-25A Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.324 Inches Minimum And 0.364 Inches Maximum  |
| <b>Fastener Length:</b>                               | 1.584 Inches Minimum And 1.604 Inches Maximum  |
| <b>Head Style:</b>                                    | Button   |
| <b>Head Diameter:</b>                                 | 0.365 Inches Minimum And 0.385 Inches Maximum  |
| <b>Head Height:</b>                                   | 0.083 Inches Minimum And 0.103 Inches Maximum  |
| <b>Grip Diameter:</b>                                 | 0.184 Inches Minimum And 0.186 Inches Maximum  |
| <b>Groove Diameter:</b>                               | 0.136 Inches Minimum And 0.146 Inches Maximum  |
| <b>Single Shear Strength:</b>                         | 2125 Pounds Per Square Inch  |
| <b>Internal Drive Style:</b>                          | Slot   |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Grip Length:</b>                                   | 1.5937 Inches Nominal  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 125000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                               | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unf  |

## How to Order

Order this clevis bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN23-25A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.