

## **P/N AN23-28**

### **Description**

length: 1-25-32", grip: 1-7/16", thread: 10-32, cadmium plated steel drilled shank

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: AN2328

Minimum Qty (MOQ): 5

NSN: 5306-00-151-2307

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N AN23-28 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.324 Inches Minimum And 0.364 Inches Maximum
Fastener Length:	1.771 Inches Minimum And 1.791 Inches Maximum
Head Style:	Button
Head Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Head Height:	0.083 Inches Minimum And 0.103 Inches Maximum
Groove Diameter:	0.136 Inches Minimum And 0.146 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.136 Inches Minimum First Hole And 0.146 Inches Maximum First Hole
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec 5th Treatment Response Overall
Thread Series Designator:	Unf

## **How to Order**

Order this clevis bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/clevis+bolts/AN23-28">https://military-fasteners.com/bolts/clevis+bolts/AN23-28</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/clevis+bolts/AN23-28">https://military-fasteners.com/bolts/clevis+bolts/AN23-28</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/clevis+bolts/AN23-28">https://military-fasteners.com/bolts/clevis+bolts/AN23-28</a> and selecting the quantity you want then click "add to cart".