

P/N AN23-31

Military-Fasteners.com

Description

length: 1-31/32", grip: 1-5/8", thread: 10-32, cadmium plated steel drilled shank

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | AN2331 |
|-------------------------|---|
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-151-2310 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N AN23-31 Specifications

| Thread Class: | За |
|---|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.297 Inches Minimum |
| Fastener Length: | 1.969 Inches Nominal |
| Head Style: | Button |
| Head Diameter: | 0.359 Inches Minimum And 0.391 Inches Maximum |
| Head Height: | 0.078 Inches Minimum And 0.110 Inches Maximum |
| Groove Diameter: | 0.141 Inches Nominal |
| Shank Unthreaded Hole Diameter: | 0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole |
| Single Shear Strength: | 2125 Pounds Per Square Inch |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Distance From Head Largest | |
| Bearing Surface To Shank Hole Center: | 1.813 Inches Nominal First Hole |
| Material: | Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall |
| Material Document And Classification: | Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |
| Departure From Cited Document: | Thread T Per Mil-s-7742 Except Major D1a Is Not To Exceed Max Allow Bolt Shank D1a |
| | |

How to Order

Order this clevis bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/clevis+bolts/AN23-31</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.