

Description

length: 2-5/32", grip: 1-13/16", thread: 10-32, cadmium plated steel, undrilled shank, AN23 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN2334A
Minimum Qty (MOQ):	20
NSN:	5306-00-150-9922
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN23-34A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.297 Inches Minimum
Fastener Length:	2.156 Inches Nominal
Head Style:	Button
Head Diameter:	0.359 Inches Minimum And 0.391 Inches Maximum
Head Height:	0.078 Inches Minimum And 0.110 Inches Maximum
Groove Diameter:	0.141 Inches Nominal
Single Shear Strength:	2125 Pounds Per Square Inch
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Material:	Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf
Departure From Cited Document:	Thread T Per Mil-s-7742 Except Major Dia Is Not To Exceed Max Allow Bolt Shank Dia

How to Order

Order this clevis bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN23-34A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.