

Description

length: 2-25/32", grip: 2-7/16", thread: 10-32, cadmium plated steel, drilled shank, AN23 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN2344
Minimum Qty (MOQ):	10
NSN:	5306-00-151-2393
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN23-44 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.344 Inches Nominal
Fastener Length:	2.781 Inches Nominal
Head Style:	Button
Head Diameter:	0.375 Inches Nominal
Head Height:	0.094 Inches Nominal
Groove Diameter:	0.047 Inches Nominal
Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Single Shear Strength:	2125 Pounds Per Square Inch
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.625 Inches Minimum First Hole And 2.641 Inches Maximum First Hole
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Cadmium Overall And Dichromate Overall
Thread Series Designator:	Unf

How to Order

Order this clevis bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN23-44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.