

Description

length: 2-25/32", grip: 2-7/16", thread: 10-32, cadmium plated steel, drilled shank, AN23 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN2344 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5306-00-151-2393 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N AN23-44 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.344 Inches Nominal |
| Fastener Length: | 2.781 Inches Nominal |
| Head Style: | Button |
| Head Diameter: | 0.375 Inches Nominal |
| Head Height: | 0.094 Inches Nominal |
| Groove Diameter: | 0.047 Inches Nominal |
| Shank Unthreaded Hole Diameter: | 0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole |
| Single Shear Strength: | 2125 Pounds Per Square Inch |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 2.625 Inches Minimum First Hole And 2.641 Inches Maximum First Hole |
| Material: | Steel Corrosion Resisting Overall |
| Surface Treatment: | Cadmium Overall And Dichromate Overall |
| Thread Series Designator: | Unf |

How to Order

Order this clevis bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN23-44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.