

**Description**

length: 2-25/32", grip: 2-7/16", thread: 10-32, cadmium plated steel, drilled shank, AN23 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN2344
Minimum Qty (MOQ):	10
NSN:	5306-00-151-2393
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N AN23-44 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.344 Inches Nominal
<b>Fastener Length:</b>	2.781 Inches Nominal
<b>Head Style:</b>	Button
<b>Head Diameter:</b>	0.375 Inches Nominal
<b>Head Height:</b>	0.094 Inches Nominal
<b>Groove Diameter:</b>	0.047 Inches Nominal
<b>Shank Unthreaded Hole Diameter:</b>	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
<b>Single Shear Strength:</b>	2125 Pounds Per Square Inch
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	2.625 Inches Minimum First Hole And 2.641 Inches Maximum First Hole
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Surface Treatment:</b>	Cadmium Overall And Dichromate Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this clevis bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN23-44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.