

**Description**

length: 1-7/32", grip: 7/8", thread: 1/4-28, cadmium plated steel, undrilled shank, AN24 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN2419A
Minimum Qty (MOQ):	10
NSN:	5306-00-156-2288
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N AN24-19A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.344 Inches Nominal
<b>Fastener Length:</b>	1.219 Inches Nominal
<b>Head Style:</b>	Button
<b>Head Diameter:</b>	0.500 Inches Nominal
<b>Head Height:</b>	0.125 Inches Nominal
<b>Groove Diameter:</b>	0.0470 Inches Nominal
<b>Single Shear Strength:</b>	3680 Pounds Per Square Inch
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this clevis bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN24-19A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.