

Description

length: 1-11/32", grip: 1", thread: 1/4-28, cadmium plated steel drilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN2421
Minimum Qty (MOQ):	5
NSN:	5306-00-151-0523
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN24-21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.226 Inches Minimum
Fastener Length:	1.344 Inches Nominal
Head Style:	Button
Head Diameter:	0.500 Inches Nominal
Head Height:	0.125 Inches Nominal
Groove Diameter:	0.191 Inches Minimum And 0.201 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.172 Inches Minimum First Hole And 1.204 Inches Maximum First Hole
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf

How to Order

Order this clevis bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN24-21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.