

**Description**

length: 1-15/32", grip: 1-1/8", thread: 1/4-28, cadmium plated steel drilled shank

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN2423
Minimum Qty (MOQ):	10
NSN:	5306-00-151-0525
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N AN24-23 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.324 Inches Minimum And 0.364 Inches Maximum
<b>Fastener Length:</b>	1.459 Inches Minimum And 1.479 Inches Maximum
<b>Head Style:</b>	Button
<b>Head Diameter:</b>	0.484 Inches Minimum And 0.516 Inches Maximum
<b>Head Height:</b>	0.109 Inches Minimum And 0.141 Inches Maximum
<b>Groove Diameter:</b>	0.191 Inches Minimum And 0.201 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.066 Inches Minimum First Hole And 0.076 Inches Maximum First Hole
<b>Single Shear Strength:</b>	3680 Pounds Per Square Inch
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	1.297 Inches Minimum First Hole And 1.328 Inches Maximum First Hole
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this clevis bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN24-23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.