

Description

length: 1-17/32", grip: 1-3/16", thread: 1/4-28, cadmium plated steel drilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN2424
Minimum Qty (MOQ):	5
NSN:	5306-00-151-0526
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN24-24 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Minimum And 0.363 Inches Maximum
Fastener Length:	1.521 Inches Minimum And 1.541 Inches Maximum
Head Style:	Button
Head Diameter:	0.500 Inches Nominal
Head Height:	0.125 Inches Nominal
Groove Diameter:	0.047 Inches Nominal
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Single Shear Strength:	3680 Pounds Per Square Inch
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.375 Inches Nominal First Hole
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unf

How to Order

Order this clevis bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN24-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.