

**Description**

length: 1-17/32", grip: 1-3/16", thread: 1/4-28, cadmium plated steel drilled shank

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN2424
Minimum Qty (MOQ):	5
NSN:	5306-00-151-0526
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N AN24-24 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Minimum And 0.363 Inches Maximum
<b>Fastener Length:</b>	1.521 Inches Minimum And 1.541 Inches Maximum
<b>Head Style:</b>	Button
<b>Head Diameter:</b>	0.500 Inches Nominal
<b>Head Height:</b>	0.125 Inches Nominal
<b>Groove Diameter:</b>	0.047 Inches Nominal
<b>Shank Unthreaded Hole Diameter:</b>	0.076 Inches Nominal First Hole
<b>Single Shear Strength:</b>	3680 Pounds Per Square Inch
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	1.375 Inches Nominal First Hole
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this clevis bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN24-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.