

## Description

length: 2-1/32", grip: 1-11/16", thread: 1/4-28, cadmium plated steel undrilled shank

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	AN2432A
Minimum Qty (MOQ):	1
NSN:	5306-00-156-2391
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N AN24-32A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.272 Inches Minimum
<b>Fastener Length:</b>	2.031 Inches Nominal
<b>Head Style:</b>	Button
<b>Head Diameter:</b>	0.500 Inches Nominal
<b>Head Height:</b>	0.125 Inches Nominal
<b>Groove Diameter:</b>	0.191 Inches Minimum And 0.201 Inches Maximum
<b>Single Shear Strength:</b>	3680 Pounds Per Square Inch
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this clevis bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN24-32A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.