

**Description**

Fastener Length: 23/32", Thread: 1/4-24, Thread Length: 3/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN2511A                                   |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-151-3525                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N AN25-11A Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.214 Inches Minimum   |
| <b>Fastener Length:</b>                               | 0.734 Inches Nominal   |
| <b>Head Style:</b>                                    | Button   |
| <b>Head Diameter:</b>                                 | 0.625 Inches Nominal   |
| <b>Head Height:</b>                                   | 0.156 Inches Nominal   |
| <b>Groove Diameter:</b>                               | 0.245 Inches Minimum And 0.255 Inches Maximum  |
| <b>Internal Drive Style:</b>                          | Slot   |
| <b>Nominal Thread Diameter:</b>                       | 0.312 Inches   |
| <b>Thread Quantity Per Inch:</b>                      | 24   |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall   |
| <b>Material Document And Classification:</b>          | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN25-11A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.