

P/N AN25-20

Description

length: 1-19/64", grip: 15/16", thread: 5/16-24, cadmium plated steel, drilled shank

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: AN2520

Minimum Qty (MOQ): 10

NSN: 5306-00-144-3856

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N AN25-20 Specifications

3a
Right-hand
0.297 Inches Minimum
1.297 Inches Nominal
Button
0.609 Inches Minimum And 0.641 Inches Maximum
0.140 Inches Minimum And 0.172 Inches Maximum
0.250 Inches Nominal
0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
5750 Pounds Per Square Inch
Slot
0.312 Inches
24
1.126 Inches Nominal First Hole
Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Unf
Thread T Per Mil-s-7742 Except Major Dia Is Not To Exceed Max Allow Shank Bolt Dia

How to Order

Order this clevis bolt from our inventory online by visiting https://military-fasteners.com/bolts/clevis+bolts/AN25-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/clevis+bolts/AN25-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/clevis+bolts/AN25-20 and selecting the quantity you want then click "add to cart".