

**Description**

Fastener Length: 1-11/32", Thread: 1/4-24, Thread Length: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN2521                                    |
| Minimum Qty (MOQ):      | 2   |
| NSN:                    | 5306-00-144-3857                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N AN25-21 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>  | Right-hand   |
| <b>Thread Length:</b>   | 0.277 Inches Minimum   |
| <b>Fastener Length:</b>   | 1.359 Inches Nominal   |
| <b>Head Style:</b>  | Button   |
| <b>Head Diameter:</b>   | 0.625 Inches Nominal   |
| <b>Head Height:</b>   | 0.156 Inches Nominal   |
| <b>Groove Diameter:</b>   | 0.245 Inches Minimum And 0.255 Inches Maximum  |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole  |
| <b>Single Shear Strength:</b>   | 5750 Pounds Per Square Inch  |
| <b>Internal Drive Style:</b>  | Slot   |
| <b>Nominal Thread Diameter:</b>   | 0.312 Inches   |
| <b>Thread Quantity Per Inch:</b>  | 24   |
| <b>Minimum Tensile Strength:</b>  | 125000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>   | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 1.172 Inches Minimum First Hole And 1.203 Inches Maximum First Hole  |
| <b>Material:</b>  | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall |
| <b>Surface Treatment:</b>   | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b>                   | Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall  |
| <b>Thread Series Designator:</b>  | Unf  |

## How to Order

Order this clevis bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN25-21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.