

P/N AN25-22

Description

length: 1-27/64", grip: 1-1/16", thread: 5/16-24, cadmium plated steel, drilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: AN2522

Minimum Qty (MOQ): 5

NSN: 5306-00-144-3858

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN25-22 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.340 Inches Minimum And 0.380 Inches Maximum
Fastener Length:	1.412 Inches Minimum And 1.432 Inches Maximum
Head Style:	Button
Head Diameter:	0.609 Inches Minimum And 0.641 Inches Maximum
Head Height:	0.140 Inches Minimum And 0.172 Inches Maximum
Groove Diameter:	0.245 Inches Minimum And 0.255 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Single Shear Strength:	5750 Pounds Per Square Inch
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.235 Inches Minimum First Hole And 1.265 Inches Maximum First Hole
Material:	Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-5626 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-8695 Mil Spec 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf
Departure From Cited Document:	Thread T Per Mil-s-7742 Except Major Dia Is Not To Exceed Max Allow Shank Bolt Dia

How to Order

Order this clevis bolt from our inventory online by visiting https://military-fasteners.com/bolts/clevis+bolts/AN25-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/clevis+bolts/AN25-22 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/clevis+bolts/AN25-22 and selecting the quantity you want then click "add to cart".