

Description

Fastener Length: 2-3/16", Thread: 1/4-24, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN2534A
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-151-3543
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN25-34A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.328 Inches Minimum And 0.392 Inches Maximum
Fastener Length:	2.156 Inches Minimum And 2.188 Inches Maximum
Head Style:	Button
Head Diameter:	0.609 Inches Minimum And 0.641 Inches Maximum
Head Height:	0.141 Inches Minimum And 0.172 Inches Maximum
Groove Diameter:	0.245 Inches Minimum And 0.255 Inches Maximum
Single Shear Strength:	5750 Pounds Per Square Inch
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Departure From Cited Document:	Thread T Per Mil-s-7742 Except Major Dia Is Not To Exceed Max Allow Shank Bolt Dia

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN25-34A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.