

Description

Thread Size: 1/4", Nut Length: 7/8", Nut Height: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	AN256F10
Minimum Qty (MOQ):	2
NSN:	5310-00-207-9316
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc

NO IMAGE
AVAILABLE

P/N AN256F10 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.890 Inches Nominal
Distance From Base To Center Of Aperture:	0.281 Inches Nominal
Nut Height:	0.313 Inches Nominal
Plate Thickness:	0.062 Inches Minimum
Plate Width:	0.438 Inches Nominal
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Mounting Hole Center To Base:	0.141 Inches Nominal
Center To Center Distance Between Mounting Holes Along Length:	0.247 Inches Minimum And 0.253 Inches Maximum
Thread Series:	Unf
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.190 Inches
Material:	Plastic Polyamide Locking Insert Or Fiber Locking Insert
Material:	Steel Nut
Material:	Plastic Polyamide Or Fiber Locking Insert

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/AN256F10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.