



Military-Fasteners.com

P/N AN256F6

Description

Thread: 6-32, Thread Size: 1/8", Nut Length: 7/8", Nut Height: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN256F6
Minimum Qty (MOQ):	1
NSN:	5310-00-207-9319
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN256F6 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design Or Prevailing Torque With Nonmetallic Insert
Mounting Hole Diameter:	0.098 Inches Minimum And 0.103 Inches Maximum
Nut Style:	Plate
Nut Length:	0.875 Inches Minimum And 0.905 Inches Maximum
Distance From Base To Center Of Aperture:	0.266 Inches Minimum And 0.296 Inches Maximum
Nut Height:	0.298 Inches Minimum And 0.328 Inches Maximum
Plate Thickness:	0.062 Inches Minimum
Plate Width:	0.423 Inches Minimum And 0.453 Inches Maximum
Nut Mounting Provision:	Straight Holes
Mounting Hole Arrangement Style:	2 Holes
Distance From Mounting Hole Center To Base:	0.453 Inches Minimum And 0.483 Inches Maximum
Center To Center Distance Between Mounting Holes Along Length:	0.247 Inches Minimum And 0.253 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall

How to Order

Order this self-locking nutplate from our inventory online by visiting <https://military-fasteners.com/nuts/locknuts/AN256F6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.