

Description

length: 1-51/64", grip: 1-7/16", thread: 5/16-24, cadmium plated steel drilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN2628
Minimum Qty (MOQ):	2
NSN:	5306-00-151-3112
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N AN26-28 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.781 Inches Minimum
Fastener Length:	1.781 Inches Minimum And 1.812 Inches Maximum
Head Style:	Button
Head Diameter:	0.672 Inches Minimum And 0.703 Inches Maximum
Head Height:	0.172 Inches Minimum And 0.203 Inches Maximum
Groove Diameter:	0.308 Inches Minimum And 0.318 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Single Shear Strength:	8280 Pounds Per Square Inch
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.641 Inches Minimum First Hole And 1.672 Inches Maximum First Hole
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this clevis bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN26-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.