

**Description**

Fastener Length: 2-35/64", Thread: 3/8-24, Thread Length: 1/4

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN2640
Minimum Qty (MOQ):	1
NSN:	5306-00-151-2652
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N AN26-40 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.276 Inches Minimum
<b>Fastener Length:</b>	2.547 Inches Nominal
<b>Head Style:</b>	Button
<b>Head Diameter:</b>	0.688 Inches Nominal
<b>Head Height:</b>	0.188 Inches Nominal
<b>Groove Diameter:</b>	0.308 Inches Minimum And 0.318 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
<b>Single Shear Strength:</b>	8280 Pounds Per Square Inch
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	2.391 Inches Minimum First Hole And 2.422 Inches Maximum First Hole
<b>Material:</b>	Steel Comp 4130 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this clevis bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN26-40> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.