

Description

Fastener Length: 2-35/64", Thread: 3/8-24, Thread Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | AN2640 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5306-00-151-2652 |
| Schedule B: | 7318.15.2010 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N AN26-40 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.276 Inches Minimum |
| Fastener Length: | 2.547 Inches Nominal |
| Head Style: | Button |
| Head Diameter: | 0.688 Inches Nominal |
| Head Height: | 0.188 Inches Nominal |
| Groove Diameter: | 0.308 Inches Minimum And 0.318 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole |
| Single Shear Strength: | 8280 Pounds Per Square Inch |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.375 Inches |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 2.391 Inches Minimum First Hole And 2.422 Inches Maximum First Hole |
| Material: | Steel Comp 4130 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this clevis bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN26-40> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.