

P/N AN26-44

Description

Fastener Length: 2-51/64", Thread: 3/8-24, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AN2644
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-151-2654
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N AN26-44 Specifications

Thread Direction: Right-hand Thread Length: 0.276 Inches Minimum Fastener Length: 2.797 Inches Nominal Head Style: Button Head Diameter: 0.688 Inches Nominal Head Height: 0.188 Inches Nominal Head Height: 0.308 Inches Minimum And 0.318 Inches Maximum Groove Diameter: 0.308 Inches Minimum And 0.318 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole Single Shear Strength: 0.375 Inches Internal Drive Style: 0.375 Inches Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 0.500 Pounds Per Square Inch Hardness Rating: 0.500 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 8130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Material Response Overall Or Milis-6039 Mil Spec 3rd Material Response Overall Or Milis-6030 Milis		
Thread Length: 0.276 Inches Minimum Fastener Length: 2.797 Inches Nominal Head Style: Button Head Diameter: 0.688 Inches Nominal Head Height: 0.188 Inches Nominal Groove Diameter: 0.308 Inches Minimum And 0.318 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole Single Shear Strength: 8280 Pounds Per Square Inch Internal Drive Style: Slot Nominal Thread Diameter: 0.375 Inches Thread Quantity Per Inch: 24 Hardness Rating: 125000 Pounds Per Square Inch Distance From Head Largest Bearing Surface To Shank Hole Center: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Material: 26.41 Inches Minimum First Hole And 2.672 Inches Maximum First Hole Material Document And Classification: Mili-s-5626 Mil Spec 1st Material Response Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Mili-s-6050 Mil Spec 3rd Material Response Overall Or Mili-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mili-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mili-s-6098 Mil Spec Spec Single Treatment Response Overall Or Mili-s-6098 Mil Spec 3rd	Thread Class:	3a
Fastener Length: 2.797 Inches Nominal Head Style: Button Head Diameter: 0.688 Inches Nominal Head Height: 0.188 Inches Nominal Groove Diameter: 0.308 Inches Minimum And 0.318 Inches Maximum Groove Diameter: 0.308 Inches Minimum And 0.318 Inches Maximum Shank Unthreaded Hole Dlameter: 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole Single Shear Strength: 8280 Pounds Per Square Inch Internal Drive Style: Slot Nominal Thread Diameter: 0.375 Inches Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 26.4 Inches Minimum First Hole And 2.672 Inches Maximum First Hole Material: 36.4 Inches Minimum First Hole And 2.672 Inches Maximum First Hole Material Pocument And Classification: 36.5 Mil-s-5626 Mil Spec 1st Material Response Overall Or Steel Comp 8730 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Steel Comp 4037 Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec Single Treatment Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall	Thread Direction:	Right-hand
Head Style: Button Head Diameter: 0.688 Inches Nominal Head Height: 0.188 Inches Nominal Groove Diameter: 0.308 Inches Niminum And 0.318 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Minimum And 0.318 Inches Maximum First Hole Single Shear Strength: 8280 Pounds Per Square Inch Internal Drive Style: 0.375 Inches Internal Drive Style: 0.375 Inches Thread Quantity Per Inch: 24 Minimum Tensile Strength: 25000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 2.641 Inches Minimum First Hole And 2.672 Inches Maximum First Hole Material: 3641 Inches Minimum First Hole And 2.672 Inches Maximum First Hole Overall Or Steel Comp 4037 Overall Mili-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: 26mium Overall And Chromate Overall Surface Treatment Document And Classification: 29c-9-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Thread Length:	0.276 Inches Minimum
Head Diameter: 0.688 Inches Nominal Head Height: 0.188 Inches Nominal Grove Diameter: 0.308 Inches Minimum And 0.318 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole Single Shear Strength: 8280 Pounds Per Square Inch Internal Drive Style: Slot Nominal Thread Diameter: 0.375 Inches Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 0.500 Pounds Per Square Inch Hardness Rating: 0.600 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Seel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Material Document And Classification: Siele Comp 4140 Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6090 Assn Std 6th Material Response Overall Or Steel Comp 4140 Chromate Overall Surface Treatment Document And Classification: Q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Fastener Length:	2.797 Inches Nominal
Head Height: 0.188 Inches Nominal Groove Diameter: 0.308 Inches Minimum And 0.318 Inches Maximum Shank Unthreaded Hole Diameter: 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole Single Shear Strength: 8280 Pounds Per Square Inch Internal Drive Style: Slot Nominal Thread Diameter: 0.375 Inches Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 0.6.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 261 Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Miles-5626 Mil Spec 1st Material Response Overall Or Miles-6049 Mil Spec 2nd Material Response Overall Or Miles-6050 Mil Spec 3rd Material Response Overall Or Miles-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: 0q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Head Style:	Button
Groove Diameter: 5 hank Unthreaded Hole Diameter: 5 lot Nominal Thread Diameter: 5 lot 1 lotses Minimum First Hole 1 lotses Verall C Minimum Overall And 32.0 Rockwell C Maximum Overall 1 lotsence From Head Largest Bearing 5 urface To Shank Hole Center: 5 lote Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mill-s-5626 Mill Spec 1st Material Response Overall Or Mil-s-6049 Mill Spec 2nd Material Response Overall Or Mil-s-6050 Mill Spec 3rd Material Response Overall Or Mil-s-6098 Mill Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment Document And Classification: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Cadmium Overall And Chromate Overall	Head Diameter:	0.688 Inches Nominal
Shank Unthreaded Hole Diameter:0.106 Inches Minimum First Hole And 0.116 Inches Maximum First HoleSingle Shear Strength:8280 Pounds Per Square InchInternal Drive Style:SlotNominal Thread Diameter:0.375 InchesThread Quantity Per Inch:24Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:2.641 Inches Minimum First Hole And 2.672 Inches Maximum First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Head Height:	0.188 Inches Nominal
Single Shear Strength: 8280 Pounds Per Square Inch Internal Drive Style: Slot Nominal Thread Diameter: 0.375 Inches Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 26.41 Inches Minimum First Hole And 2.672 Inches Maximum First Hole Material: 5teel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment Document And Classification: 0q-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Groove Diameter:	0.308 Inches Minimum And 0.318 Inches Maximum
Internal Drive Style: Nominal Thread Diameter: 0.375 Inches Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Pocument And Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Oq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Nominal Thread Diameter: 0.375 Inches Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 2.641 Inches Minimum First Hole And 2.672 Inches Maximum First Hole Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mili-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Single Shear Strength:	8280 Pounds Per Square Inch
Thread Quantity Per Inch:24Minimum Tensile Strength:125000 Pounds Per Square InchHardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:2.641 Inches Minimum First Hole And 2.672 Inches Maximum First HoleMaterial:Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Internal Drive Style:	Slot
Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 2.641 Inches Minimum First Hole And 2.672 Inches Maximum First Hole Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.375 Inches
Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Material Document And Classification: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall 2.641 Inches Minimum First Hole And 2.672 Inches Maximum First Hole Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	24
Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Pocument And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment Oq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material: Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Distance From Head Largest Bearing Surface To Shank Hole Center:	2.641 Inches Minimum First Hole And 2.672 Inches Maximum First Hole
Material Document And Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment Document And Classification: Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Ams 6300 Assn	Material:	
Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Material Document And Classification:	Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 6th Material Response
Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator.	Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/clevis+bolts/AN26-44 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/clevis+bolts/AN26-44 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/clevis+bolts/AN26-44 and selecting the quantity you want then click "add to cart".