

P/N AN3-3

Description

Length: 15/32", grip: 1/16", thread: 10-32, cadmium plated steel, drilled shank, airframe bolt, AN3 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information


SKU / Model: AN33

Minimum Qty (MOQ): 50

NSN: 5306-00-151-3015

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N AN3-3 Specifications

Thread Direction: Right-hand Thread Length: 0.407 Inches Minimum Fastener Length: 0.409 Inches Nominal Head Style: Hexagon Head Height: 0.109 Inches Minimum And 0.141 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Midth Between Flats: 0.109 Inches Mominal First Hole Nominal Thread Diameter: 0.190 Inches Nominal First Hole Nominal Thread Diameter: 0.190 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 32 Material Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6048 Mil Spec 5th Material Response Overall Or Mil-s-6058 Mil Spec 5th Material Response Overal		
Thread Length: 0.469 Inches Minimum Fastener Length: 0.469 Inches Nominal Head Style: Hexagon Head Height: 0.109 Inches Minimum And 0.141 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Nominal Thread Diameter: 0.070 Inches Nominal First Hole Nominal Thread Diameter: 0.190 Inches Grip Length: 0.062 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Material Document And Classification: Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Steel Material Response Overall Or Mil-s-6566 Mil Spec 5th Material Response Overall Or Mil-s-6568 Mil Spec Sth Material Response Overall Or Mil-s	Thread Class:	3a
Fastener Length: 0.469 Inches Nominal Head Style: Hexagon Head Height: 0.109 Inches Minimum And 0.141 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Shank Unthreaded Hole Diameter: 0.070 Inches Nominal First Hole Nominal Thread Diameter: 0.190 Inches Grip Length: 0.062 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Asserting Surface To Shank Hole Center: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Material Document And Classification: Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6058 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mi	Thread Direction:	Right-hand
Head Style: Hexagon Head Height: 0.109 Inches Minimum And 0.141 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Shank Unthreaded Hole Diameter: 0.070 Inches Nominal First Hole Nominal Thread Diameter: 0.190 Inches Grip Length: 0.062 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 0.328 Inches Nominal First Hole Center: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall	Thread Length:	0.407 Inches Minimum
Head Height: 0.109 Inches Minimum And 0.141 Inches Maximum Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum 0.070 Inches Nominal First Hole 0.070 Inches Nominal First Hole 0.190 Inches Grip Length: 0.062 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 0.328 Inches Nominal First Hole Center: Material: Material: Material Document And Classification: Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6059 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th	Fastener Length:	0.469 Inches Nominal
Width Between Flats: 0.365 Inches Minimum And 0.377 Inches Maximum Shank Unthreaded Hole Diameter: 0.070 Inches Nominal First Hole Nominal Thread Diameter: 0.190 Inches Grip Length: 0.062 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Material Document And Classification: Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6056 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6056 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6056 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or M	Head Style:	Hexagon
Shank Unthreaded Hole Diameter: Nominal Thread Diameter: 0.190 Inches 0.062 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5t	Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Nominal Thread Diameter: 0.190 Inches Grip Length: 0.062 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec Std Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overall Or Mil-s-6050 Mil Spec 5th Material Response Overal	Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Grip Length: 0.062 Inches Nominal Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 0.328 Inches Nominal First Hole Center: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Material Document And Classification: Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil S	Shank Unthreaded Hole Diameter:	0.070 Inches Nominal First Hole
Features Provided: Finished Head Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Material Document And Classification: Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall	Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch: Minimum Tensile Strength: 125000 Pounds Per Square Inch Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall	Grip Length:	0.062 Inches Nominal
Minimum Tensile Strength: Hardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall	Features Provided:	Finished Head
Hardness Rating: Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Material Document And Classification: Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall	Thread Quantity Per Inch:	32
Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Bearing Surface To Shank Hole Center: Material: Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall Or Steel Comp 4130 Overall Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material: Overall Or Steel Comp 4130 Overall Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall	Distance From Head Largest Bearing Surface To Shank Hole Center:	0.328 Inches Nominal First Hole
Material Document And Classification: Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall	Material:	
Surface Treatment: Cadmium Overall And Chromate Overall	Material Document And Classification:	Material Response Overall Or Ams 6300 Assn Std 4th Material Response Overall Or Mil-s-5626 Mil Spec 5th Material Response Overall Or
	Surface Treatment:	Cadmium Overall And Chromate Overall
Og-p-416 Tv 2 Cl 3 Fed Spec All Treatment Responses Overall	Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator: Unf	Thread Series Designator:	Unf
	•	

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/AN3-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/AN3-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/AN3-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/AN3-3 and selecting the quantity you want then click "add to cart".