

Description

Fastener Length: 3-27/64", Thread: 3/4-16, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN3254A
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-050-9641
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N AN32-54A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	3.422 Inches Minimum And 3.453 Inches Maximum
Head Style:	Button
Head Diameter:	1.297 Inches Minimum And 1.328 Inches Maximum
Head Height:	0.359 Inches Minimum And 0.391 Inches Maximum
Groove Diameter:	0.655 Inches Minimum And 0.665 Inches Maximum
Single Shear Strength:	33150 Pounds Per Square Inch
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.750 Inches
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/clevis+bolts/AN32-54A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.