

Description

grip: 1-1/4", thread: 10-32, with cotter pin hole

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN386110
Minimum Qty (MOQ):	5
NSN:	5315-00-198-8098
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N AN386-1-10 Specifications

First End Style:	Oval
Second End Style:	Oval
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.562 Inches Minimum
Taper Length:	1.250 Inches Minimum And 1.375 Inches Maximum
Taper Minor Diameter:	0.203 Inches Nominal
Taper Major Diameter:	0.207 Inches Nominal
Hole Arrangement Style:	Drilled Shank Threaded Pin
First Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Distance From Centerline Of Hole To End Of Pin:	1.562 Inches Nominal
Grip Length:	1.250 Inches Nominal
Second End Relationship With First End:	Not Identical
Nominal Thread Size:	0.190 Inches
Taper:	0.500 Per Foot In Inches
First End Location:	Unthreaded End
First End Outer Radius:	0.015 Inches Nominal
Second End Outer Radius:	0.015 Inches Nominal
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Style Designator:	Threaded At Small End
Thread Series Designator:	Unf

How to Order

Order this threaded tapered pin from our inventory online by visiting <https://military-fasteners.com/pins/threaded+tapered+pins/AN386-1-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.