

Description

Thread Size: 1/4", Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN386113
Minimum Qty (MOQ):	5 EA
NSN:	5315-00-282-0198
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N AN386-1-13 Specifications

First End Style:	Square
Second End Style:	Square
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.422 Inches Minimum And 0.454 Inches Maximum
Taper Length:	1.734 Inches Minimum And 1.766 Inches Maximum
Taper Minor Diameter:	0.203 Inches Minimum And 0.207 Inches Maximum
Taper Major Diameter:	0.277 Inches Nominal
Hole Arrangement Style:	One End Drilled
First Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Distance From Centerline Of Hole To End Of Pin:	0.109 Inches Minimum And 0.141 Inches Maximum
Grip Length:	1.609 Inches Minimum And 1.641 Inches Maximum
Second End Relationship With First End:	Not Identical
Nominal Thread Size:	0.190 Inches
Taper:	0.500 Per Foot In Inches
First End Location:	Threaded End
Material:	Steel Comp 4037 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Threaded At Small End
Thread Series Designator:	Unf

How to Order

Order this pin from our inventory online by visiting <https://military-fasteners.com/pins/threaded+tapered+pins/AN386-1-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.