

P/N AN386-1-6A

Description

grip: 3/4", thread: 10-32, without cotter pin hole, fine thread, cadmium plated, AN386 series pin

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN38616A
Minimum Qty (MOQ):	5
NSN:	5315-00-198-8091
Schedule B:	7318.24.0000

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9









^{*} See page 2 for technical characteristics

P/N AN386-1-6A Specifications

First End Style:	Oval
Second End Style:	Square
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.422 Inches Minimum And 0.453 Inches Maximum
Taper Length:	0.859 Inches Minimum And 0.891 Inches Maximum
Taper Minor Diameter:	0.203 Inches Minimum And 0.207 Inches Maximum
Taper Major Diameter:	0.242 Inches Nominal
Grip Length:	0.734 Inches Minimum And 0.766 Inches Maximum
Second End Relationship With First End:	Not Identical
Nominal Thread Size:	0.190 Inches
Taper:	0.500 Per Foot In Inches
First End Location:	Oval End
Material:	Steel Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Qq-s-681 Fed Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Threaded At Small End
Thread Series Designator:	Unf

How to Order

Order this threaded tapered pin from our inventory online by visiting https://military-fasteners.com/pins/threaded+tapered+pins/AN386-1-6A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.