

**Description**

Thread Size: 1/4", Thread Length: 1/2

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |  |
|-------------------------|--|
| SKU / Model:            | AN38617                                    |
| Minimum Qty (MOQ):      | 2  |
| NSN:                    | 5315-00-221-2733                           |
| ECCN:                   | EAR99                                      |
| National Motor Freight: | 105840, Nails / Spikes I / S Noi Plain Etc |



## P/N AN386-1-7 Specifications

|  |   |
|--|---|
| <b>First End Style:</b>                                | Oval  |
| <b>Second End Style:</b>                               | Square  |
| <b>Thread Class:</b>                                   | 3a  |
| <b>Thread Direction:</b>                               | Right-hand  |
| <b>Thread Length:</b>                                  | 0.422 Inches Minimum And 0.453 Inches Maximum   |
| <b>Taper Length:</b>                                   | 0.984 Inches Minimum And 1.016 Inches Maximum   |
| <b>Taper Minor Diameter:</b>                           | 0.203 Inches Minimum And 0.207 Inches Maximum   |
| <b>Taper Major Diameter:</b>                           | 0.240 Inches Nominal  |
| <b>Hole Arrangement Style:</b>                         | One End Drilled   |
| <b>First Hole Diameter:</b>                            | 0.070 Inches Minimum And 0.080 Inches Maximum   |
| <b>Distance From Centerline Of Hole To End Of Pin:</b> | 0.109 Inches Minimum And 0.141 Inches Maximum   |
| <b>Grip Length:</b>                                    | 0.859 Inches Minimum And 0.891 Inches Maximum   |
| <b>Second End Relationship With First End:</b>         | Not Identical   |
| <b>Nominal Thread Size:</b>                            | 0.190 Inches  |
| <b>Taper:</b>  | 0.500 Per Foot In Inches  |
| <b>First End Location:</b>                             | Threaded End  |
| <b>First End Outer Radius:</b>                         | 0.500 Inches Nominal  |
| <b>Material:</b>                                       | Steel Comp 2330 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall   |
| <b>Material Document And Classification:</b>           | Qq-s-689 Fed Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall |
| <b>Surface Treatment:</b>                              | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b>  | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall   |
| <b>Style Designator:</b>                               | Threaded At Small End   |
| <b>Thread Series Designator:</b>                       | Unf   |

## How to Order

Order this threaded tapered pin from our inventory online by visiting <https://military-fasteners.com/pins/threaded+tapered+pins/AN386-1-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.