

P/N AN386-2-9

Military-Fasteners.com

Description

Thread Size: 1/4", Thread Length: 1/2"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	AN38629
Minimum Qty (MOQ):	1 EA
NSN:	5315-00-197-3209
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N AN386-2-9 Specifications

First End Style:	Square	
Thread Class:	За	
Thread Direction:	Right-hand	
Thread Length:	0.422 Inches Minimum And 0.453 Inches Maximum	
Taper Length:	1.234 Inches Minimum And 1.266 Inches Maximum	
Taper Minor Diameter:	0.253 Inches Minimum And 0.257 Inches Maximum	
Taper Major Diameter:	0.300 Inches Nominal	
Hole Arrangement Style:	One End Drilled	
First Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum	
Distance From Centerline Of Hole To End Of Pin:	0.109 Inches Minimum And 0.141 Inches Maximum	
Grip Length:	1.109 Inches Minimum And 1.141 Inches Maximum	
Second End Relationship With First End:	Identical	
Nominal Thread Size:	0.190 Inches	
Taper:	0.500 Per Foot In Inches	
First End Location:	Threaded End	
Material:	Steel Comp 2330 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall	
Material Document And Classification:	Qq-s-689 Fed Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall	
Surface Treatment:	Cadmium Overall	
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall	
Style Designator:	Threaded At Small End	
Thread Series Designator:	Unf	

How to Order

Order this pin from our inventory online by visiting <u>https://military-fasteners.com/pins/threaded+tapered+pins/AN386-2-9</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.