

Description

grip: 1-1/4", thread: 1/4-28, without cotter pin hole

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN386310A
Minimum Qty (MOQ):	1
NSN:	5315-00-198-8126
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE
AVAILABLE

P/N AN386-3-10A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Minimum And 0.469 Inches Maximum
Taper Length:	1.359 Inches Minimum And 1.391 Inches Maximum
Taper Minor Diameter:	0.315 Inches Minimum And 0.319 Inches Maximum
Grip Length:	1.234 Inches Minimum And 1.266 Inches Maximum
Nominal Thread Size:	0.250 Inches
Material:	Steel Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Qq-s-681 Fed Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Threaded At Small End
Thread Series Designator:	Unf

How to Order

Order this threaded tapered pin from our inventory online by visiting <https://military-fasteners.com/pins/threaded+tapered+pins/AN386-3-10A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.