

Description

Thread Size: 1/4", Thread Length: 1/2",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN386314
Minimum Qty (MOQ):	5
NSN:	5315-00-200-2282
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



P/N AN386-3-14 Specifications

First End Style:	Oval
Second End Style:	Square
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Minimum And 0.469 Inches Maximum
Taper Length:	1.859 Inches Minimum And 1.891 Inches Maximum
Taper Minor Diameter:	0.315 Inches Minimum And 0.319 Inches Maximum
Taper Major Diameter:	0.395 Inches Nominal
Hole Arrangement Style:	One End Drilled
First Hole Diameter:	0.076 Inches Minimum And 0.086 Inches Maximum
Distance From Centerline Of Hole To End Of Pin:	0.109 Inches Minimum And 0.141 Inches Maximum
Grip Length:	1.734 Inches Minimum And 1.766 Inches Maximum
Second End Relationship With First End:	Not Identical
Nominal Thread Size:	0.250 Inches
Taper:	0.500 Per Foot In Inches
First End Location:	Oval End
Material:	Steel Comp 2330 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Qq-s-689 Fed Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Threaded At Small End
Thread Series Designator:	Unf

How to Order

Order this threaded tapered pin from our inventory online by visiting <https://military-fasteners.com/pins/threaded+tapered+pins/AN386-3-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.