



**MILITARY ★ FASTENERS**

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N AN386-3-17**

## Description

Thread Size: 1/4", Thread Length: 3/8", cadmium surface, fine thread, AN386 series pin

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	AN386317
Minimum Qty (MOQ):	2
NSN:	5315-00-198-8133
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N AN386-3-17 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.382 Inches Nominal
<b>Taper Length:</b>	2.234 Inches Minimum And 2.266 Inches Maximum
<b>Taper Minor Diameter:</b>	0.315 Inches Minimum And 0.319 Inches Maximum
<b>Hole Arrangement Style:</b>	One End Drilled
<b>First Hole Diameter:</b>	0.076 Inches Nominal
<b>Distance From Centerline Of Hole To End Of Pin:</b>	0.125 Inches Nominal
<b>Grip Length:</b>	2.109 Inches Minimum And 2.141 Inches Maximum
<b>Nominal Thread Size:</b>	0.250 Inches
<b>Taper:</b>	0.500 Per Foot In Inches
<b>Material:</b>	Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 4th Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	Threaded At Small End
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this threaded tapered pin from our inventory online by visiting <https://military-fasteners.com/pins/threaded+tapered+pins/AN386-3-17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.