

## **P/N AN386-3-22**

### **Description**

Thread Size: 1/4", Thread Length: 1/2", drilled shank, AN386 series pin

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	AN386322
Minimum Qty (MOQ):	5
NSN:	5315-00-140-9584
Schedule B:	7318.24.0000
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



<sup>\*</sup> See page 2 for technical characteristics

# P/N AN386-3-22 Specifications

First End Style:	Oval
Second End Style:	Oval
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.453 Inches Nominal
Taper Length:	2.875 Inches Nominal
Taper Minor Diameter:	0.315 Inches Minimum And 0.319 Inches Maximum
Taper Major Diameter:	0.500 Inches Nominal
Hole Arrangement Style:	Drilled Shank Threaded Pin
First Hole Diameter:	0.076 Inches Minimum And 0.086 Inches Maximum
Distance From Centerline Of Hole To End Of Pin:	3.203 Inches Nominal
Grip Length:	2.750 Inches Nominal
Second End Relationship With First End:	Not Identical
Nominal Thread Size:	0.250 Inches
Taper:	0.500 Per Foot In Inches
First End Location:	Unthreaded End
First End Outer Radius:	0.015 Inches Nominal
Second End Outer Radius:	0.015 Inches Nominal
Material:	Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Overall
Style Designator:	Threaded At Small End
Thread Series Designator:	Unf

# **How to Order**

