

Description

length: 15/32", grip: 1/16", thread: 10-32, corrosion resistant steel, drilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[AN3-C3](#)

SKU / Model:	AN3C3
Minimum Qty (MOQ):	10
NSN:	5306-00-145-7053
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N AN3C3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.374 Inches Minimum And 0.453 Inches Maximum
Fastener Length:	0.453 Inches Minimum And 0.500 Inches Maximum
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.377 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Grip Diameter:	0.186 Inches Minimum And 0.189 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.047 Inches Minimum And 0.078 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.312 Inches Minimum First Hole And 0.344 Inches Maximum First Hole
Material:	Steel Comp 431 Overall
Material Document And Classification:	Mil-s-18732 Mil Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN3C3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.