

**Description**

length: 17/32", grip: 1/8", thread: 10-32, corrosion resistant steel, drilled shank

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | AN3C4                                     |
| Minimum Qty (MOQ):      | 25  |
| NSN:                    | 5306-00-145-7069                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N AN3C4 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.374 Inches Minimum And 0.453 Inches Maximum                       |
| <b>Fastener Length:</b>   | 0.516 Inches Minimum And 0.562 Inches Maximum                       |
| <b>Head Style:</b>  | Hexagon   |
| <b>Head Height:</b>   | 0.109 Inches Minimum And 0.141 Inches Maximum                       |
| <b>Width Between Flats:</b>   | 0.365 Inches Minimum And 0.377 Inches Maximum                       |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole |
| <b>Nominal Thread Diameter:</b>   | 0.190 Inches  |
| <b>Grip Length:</b>   | 0.109 Inches Minimum And 0.141 Inches Maximum                       |
| <b>Features Provided:</b>   | Finished Head   |
| <b>Thread Quantity Per Inch:</b>  | 32  |
| <b>Minimum Tensile Strength:</b>  | 125000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>   | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 0.375 Inches Minimum First Hole And 0.406 Inches Maximum First Hole |
| <b>Material:</b>  | Steel Comp 431 Overall  |
| <b>Material Document And Classification:</b>                            | Mil-s-18732 Mil Spec Single Material Response Overall               |
| <b>Surface Treatment:</b>   | Passivate Overall   |
| <b>Thread Series Designator:</b>  | Unf   |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN3C4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.