

Description

Bolt part number

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | AN3C63A |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-513-9185 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N AN3C63A Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.407 Inches Minimum And 0.421 Inches Maximum |
| Fastener Length: | 6.391 Inches Minimum And 6.437 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.109 Inches Minimum And 0.141 Inches Maximum |
| Width Between Flats: | 0.365 Inches Minimum And 0.377 Inches Maximum |
| End Item Identification: | 15 Ton Vapor |
| Nominal Thread Diameter: | 0.190 Inches |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 32 |
| Special Features: | Dash Mark On Head To Denote Corrosion Resistant Steel Bolts |
| Material: | Steel Comp 431 Overall |
| Material Document And Classification: | Mil-s-18732 Mil Spec Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN3C63A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.