

**Description**

length: 29/32", grip: 1/2", thread: 10-32, corrosion resistant steel, drilled shank, AN3 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	AN3C7A
Minimum Qty (MOQ):	25
NSN:	5306-00-156-2328
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N AN3C7A Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.374 Inches Minimum And 0.453 Inches Maximum
<b>Fastener Length:</b>	0.891 Inches Minimum And 0.938 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.109 Inches Minimum And 0.141 Inches Maximum
<b>Width Between Flats:</b>	0.365 Inches Minimum And 0.377 Inches Maximum
<b>End Item Identification:</b>	Joint Stars Target Radar System;aircraft Airlifter C-17a
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.484 Inches Minimum And 0.516 Inches Maximum
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	125000 Pounds Per Square Inch
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 431 Overall
<b>Material Document And Classification:</b>	Mil-s-18732 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN3C7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.