

Description

Fastener Length: 29/64", Thread: 10-32, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	AN3DD3A
Minimum Qty (MOQ):	20
NSN:	5306-00-145-7666
ECCN:	EAR99
National Motor Freight:	013280, Alum Bolts



P/N AN3DD3A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.374 Inches Minimum And 0.453 Inches Maximum
Fastener Length:	0.453 Inches Minimum And 0.500 Inches Maximum
Head Style:	Hexagon
Head Height:	0.109 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.365 Inches Minimum And 0.377 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.052 Inches Minimum And 0.072 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Material:	Aluminum Alloy Overall
Material Document And Classification:	Qq-a-200 Fed Spec Single Material Response Overall Or Qq-a-225 Fed Spec Single Material Response Overall Or Qq-a-430 Fed Spec Single Material Response Overall
Material Document And Classification:	Qq-a-200 Fed Spec Single Material Response Or Qq-a-225 Fed Spec Single Material Response Or Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Oxide Film Overall And Anodize Overall
Surface Treatment:	Oxide Film And Anodize Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response Overall And Mil-a-8625 Mil Spec 2nd Treatment Response Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec 1st Treatment Response And Mil-a-8625 Mil Spec 2nd Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/AN3DD3A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.